Dane aktualne na dzień: 02-11-2026 04:19

Link do produktu: https://zk-teco.pl/zk-lpr-car-id-p-103.html

ZK-LPR Car ID



Cena brutto	**2 991,89 zł**
Cena netto	**2 432,43 zł**

Opis produktu

- Oprogramowanie do rozpoznawania tablic rejestracyjnych zintegrowane z kamerą
- Możliwość integracji z urządzeniami innych producentów (Milestone i Lenel)
- Identyfikuje tablice rejestracyjne z ponad 80 krajów
- Listy dostępu do konfiguracji pod kątem różnorakich imprez

Funkcja

- Umożliwia integrację z rozwiązaniami opartymi na chmurze
- Skalowalne rozwiązanie z kamerami podstawowymi i dodatkowymi
- Konwersja OCR bezpośrednio w kamerze
- Oprogramowanie LPR zintegrowane z kamerą
- Możliwość integracji z urządzeniami innych producentów (Milestone i Lenel)
- Identyfikuje tablice rejestracyjne z ponad 80 krajów
- Listy dostępu do konfiguracji pod kątem różnorakich imprez

Specyfikacja

Camera	
Image Sensor	1/2.8” Sony STAVIS CMOS
Effective Pixels	1920* 1080
Min. Illumination	Color: 0.001Lux@F1.7 (AGC ON)
Flash	512 Mb (BL-852Q38A-LP) || 1Gb / 4Gb (DL-852Q28B-LP)
IR LED No	2 (Smart IR)
IR Distance	50m
S/N Ratio	> 52dB
Lens	
Lens Type	Motorized
Mount Type	Board-in
Focal Length	3.35mm ~ 10.05mm
Aperture	F1.7 ~ F3.0
FOV	38° ~ 107°
Optical Zoom	3X
Video	
Compression	H.265+/H.265/H.264
Resolution	1080P(1920*1080)/1.3MP(1280*960)/720P(1280*720) Q720P(640*360)/CIF(352*288)
Bitrate Control	CBR/VBR
Bitrate	H.265+:1536Kbps-7Mbps H.265:1536Kbps-7Mbps H.264:1792Kbps-9Mbps
Multi-Streaming	Main Stream:1080P@25fps Sub Stream: Q720P@25fps N/A
Motion Detection	Support

Digital Zoom	Support
Audio Compression	G7.11u
Privacy Mask	5 areas
WDR	TWDR
Day/Night	Support
White Balance	Support
Defog	Support
Noise Reduction	3D DNR (BL-852Q38A-LP) || 2D/3D DNR (DL-852Q28B-LP)
Mirror/Flip	Support
Corridor Mode	Support
HLC	Support
BLC	N/A (BL-852Q38A-LP) || Support (DL-852Q28B-LP)
ROI	4 areas
Anti-flicker	Support
Network	
Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP
Interoperability	ONVIF, Profile S SDK, API
Max. Online Users	5
Web Browser	IE/Firefox/Chrome/Safari
Management Software(VMS)	AntarVis 2.0, ZKBioSecurity IVS, ZKBioAccess IVS
Operation System	Windows
Mobile APP	AntarView Pro
P2P Cloud Service	Support
Interface	
Ethernet	1 RJ-45 port (10/100Mbps)
Audio I/O	1 in / 1 out
Alarm I/O	2 in / 1 out
RS485	Support
Reset Button	Support
Micro-SD Slot	64GB (card included) (BL-852Q38A-LP) || Support (Max 128GB) (DL-852Q28B-LP)
ANR	Support
USB	N/A
General	
Power Supply	PoE (IEEE802.3af), DC 12V±10%
Power Consumption	
Ingress Protection	IP 67
Dimensions	247(L)*85(W)*76(H)mm (BL-852Q38A-LP) || Φ102*93.2 mm (DL-852Q28B-LP)
Working Humidity	10% ~ 90%
Working Temperature	-30°C ~ +60 °C
Net Weight	0.50 kg
Gross Weight	0.64 kg (BL-852Q38A-LP) || 0.70kg (DL-852Q28B-LP)